

Printing date 10/05/2021 Reviewed on 02/08/2019

1 Identification

- · Product identifier
- · Trade name: AstringedentTM, AstringedentTM X, & ViscoStatTM
- · Article number: SDS 8-001.15, 10309, 64500, 10308
- · Application of the substance / the mixture Professional Dental Hemostatic Agent
- Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Ultradent Products Inc.

505 W. Ultradent Drive (10200 S) South Jordan, UT 84095-3942

USA

onlineordersupport@ultradent.com

- · Information department: Customer Service
- · Emergency telephone number:

CHEMTREC (NORTH AMERICA) : (800) 424-9300 (INTERNATIONAL) : +(703) 527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



GHS05 Corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

- · Label elements
- · GHS label elements Void
- · Hazard pictograms GHS05, GHS07
- · Signal word Danger
- · Health Hazard-determining components of labeling:

Iron (III) Sulfate

· Hazard statements

Harmful if inhaled.

Causes severe skin burns and eye damage.

· Precautionary statements

P260 Do not breathe dusts or mists. P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/

shower.

(Contd. on page 2)

Printing date 10/05/2021 Reviewed on 02/08/2019

Trade name: AstringedentTM, AstringedentTM X, & ViscoStatTM

(Contd. of page 1)

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor. P321 Specific treatment (see on this label). P363 Wash contaminated clothing before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 3Fire = 0Reactivity = 0

· HMIS-ratings (scale 0 - 4)



*3 *Health* = *3 Fire = 0

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous co	omponents:		
10028-22-5 II	ron (III) Sulfate	♦ Skin Corr. 1A, H314; Eye Dam. 1, H318	≥5-<90%
25322-68-3 F	Polyethylene Glycol		>10- ≤ 25%
57-55-6 F	Propylene Glycol		>10- ≤ 25%
_	Trade Secret Alternative CAS number: 7631-86-9		1-10%

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. *In case of unconsciousness place patient stably in side position for transportation.*

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

Printing date 10/05/2021 Reviewed on 02/08/2019

Trade name: AstringedentTM, AstringedentTM X, & ViscoStatTM

(Contd. of page 2)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

See product labelling.

Keep receptacle tightly sealed.

· Specific end use(s) Professional Dental Hemostatic Agent

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 4)

Printing date 10/05/2021 Reviewed on 02/08/2019

Trade name: AstringedentTM, AstringedentTM X, & ViscoStatTM

(Contd. of page 3)

· Control parameters

· Compo	· Components with limit values that require monitoring at the workplace:			
10028-	10028-22-5 Iron (III) Sulfate			
REL	Long-term value: 1 mg/m³			
	as Fe			
TLV	Long-term value: 1 mg/m³			
	as Fe			
25322-	25322-68-3 Polyethylene Glycol			
WEEL	Long-term value: 10 mg/m³			
	(H); MW>200			
57-55-0	57-55-6 Propylene Glycol			
WEEL	Long-term value: 10 mg/m³			
Trade .	Trade Secret			
TWA	Short-term value: 0.8 mg/m³			

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material is based on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

(Contd. on page 5)

Printing date 10/05/2021 Reviewed on 02/08/2019

Trade name: AstringedentTM, AstringedentTM X, & ViscoStatTM

· Body protection: Protective work clothing

(Contd. of page 4)

Information on basic physical and	chemical properties	
General Information		
Appearance:	7 1	
Form:	Liquid	
Color: Odor:	According to product specification Slight iron odor	
Odor threshold:	Not determined.	
pH-value at 20 °C:	1.23-1.27	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	Undetermined	
Flash point:	Not applicable	
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 25 °C:	0.2 hPa	
Density:	Not determined	
Relative density	Not determined	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Partly miscible.	
Partition coefficient (n-octanol/wat	er): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined	
Solvent content:	.20.07	
Organic solvents:	<30 %	
Water:	<80 %	
VOC content:	10.24 %	
VOC (EC)	102.4 g/l / 0.85 lb/gal	
VOC (EC)	<30 % 10.24 %	
Solids content:	<90.0%	

Printing date 10/05/2021 Reviewed on 02/08/2019

Trade name: AstringedentTM, AstringedentTM X, & ViscoStatTM

(Contd. of page 5)

· Other information

No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions

Reacts with peroxides.

These products will react violently with peroxides so mixing with peroxides should be avoided.

- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

<i>25322-68</i>	-3 Polyethylene Glycol	
Oral	LD50	19,600 mg/kg (Guinea pig)
		17,300 mg/kg (mouse)
		>10,000 mg/kg (rat)
	LC50 Fish	>100 mg/l (Fish)
Dermal	LD50	>20,000 mg/kg (rabbit)
	LC50(Daphnia magna)	>10,000 mg/l (Water Flea) (Toxicity to aquatic invertebrates)
57-55-6 P	ropylene Glycol	
Oral	LD50	18,000 mg/kg (rabbit)
	LC50 Fish	>5,000 mg/l (Fish)
Dermal	LD50	20,800 mg/kg (rabbit)
Trade Sec	eret	
Oral	LD50	>15,000 mg/kg (mouse)
		>3,300 mg/kg (rat)
	LC50 Fish	>10,000 mg/l (Fish) (Toxicity to fish)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	0.139 mg/l (rat)

- Primary irritant effect:
- on the skin: Strong caustic effect on skin and mucous membranes.
- on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Corrosive

(Contd. on page 7)

Printing date 10/05/2021 Reviewed on 02/08/2019

Trade name: AstringedentTM, AstringedentTM X, & ViscoStatTM

(Contd. of page 6)

Irritani

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity:

57-55-6 Propylene Glycol

EC50 18,100 mg/kg (Algae)

Trade Secret

|EC50| > 1,000 mg/kg (daphnia)|

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Dispose of contents/container in accordance with international, federal, state, and local regulations.

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.

US

Printing date 10/05/2021 Reviewed on 02/08/2019

Trade name: AstringedentTM, AstringedentTM X, & ViscoStatTM

(Contd. of page 7)

Transport information	
UN-Number DOT, IMDG, IATA	UN3264
UN proper shipping name DOT IMDG, IATA	Corrosive liquid, acidic, inorganic, n.o.s. CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
Transport hazard class(es) DOT	
Toxic	
Class Label	8 Corrosive substances 6.1
IMDG, IATA	
Class Label	8 Corrosive substances 8
Packing group DOT, IMDG, IATA	II
Environmental hazards:	Not Applicable.
Special precautions for user Hazard identification number (Kemler code): EMS Number:	F- A , S - B
Segregation groups Stowage Category Stowage Code	Acids A SW2 Clear of living quarters.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not Applicable.
Transport/Additional information:	
DOT Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. 8, II

Printing date 10/05/2021 Reviewed on 02/08/2019

Trade name: AstringedentTM, AstringedentTM X, & ViscoStatTM

(Contd. of page 8)

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara

· Section 355	(extremely	hazardous	substances)):
---------------	------------	-----------	-------------	----

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

TSCA (Toxic Substances Control Act):

10028-22-5	Iron (III) Sulfate	ACTIVE
25322-68-3	Polyethylene Glycol	ACTIVE
57-55-6	Propylene Glycol	ACTIVE

· Hazardous Air Pollutants

None of the ingredients is listed.

Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

· ACGIH Carcinogenicity (American Conference of Governmental Industrial Hygienists)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Chemical safety assessment:

Device is biocompatible when used as directed by dental professionals per ISO 10993-1

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environmental, Health, and Safety
- · Contact: Customer Service
- · Date of preparation / last revision 10/05/2021 / -
- · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

Printing date 10/05/2021 Reviewed on 02/08/2019

Trade name: AstringedentTM, AstringedentTM X, & ViscoStatTM

(Contd. of page 9)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Tox. 4: Acute toxicity – Category 4 Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Eye Dam. 1: Serious eye damage/eye irritation — Category 1A

US