# according to Regulation (EC) No. 1907/2006 (REACH)

**Trade name :** Automat XR/C+ Fixer concentrate

**Revision date:** 09.09.2020 **Version (Revision):** 2.0.0 (1.0.0)

**Print date:** 16.12.2020

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

#### 1.1 Product identifier

Automat XR/C+ Fixer concentrate

# 1.2 Relevant identified uses of the substance or mixture and uses advised against

#### Relevant identified uses

Special X-ray set for Dürr developers.

#### **Products Category [PC]**

PC 30 - Photo-chemicals

#### Uses advised against

None, if handled according to order.

#### Remark

The product is intended for professional use.

# 1.3 Details of the supplier of the safety data sheet

# Supplier (manufacturer/importer/only representative/downstream user/distributor)

orochemie GmbH + Co. KG

**Street:** Max-Planck-Straße 27

Postal code/city: 70806 Kornwestheim

**Telephone:** +49 7154 1308-0 **Telefax:** +49 7154 1308-40

Information contact: DÜRR DENTAL SE, Höpfigheimer Str. 17, 74321 Bietigheim-Bissingen, Germany

Tel: +49 7142 705-0, Fax: +49 7142 705-500, info@duerrdental.com

in Great Britain/Ireland:

DÜRR DENTAL [Products] UK Ltd., 14 Linnell Way - Telford Way Industrial Estate, Kettering Northants NN16 8PS,

United Kingdom

Tel: +44 1536 526740, Fax.: +44 1536 526749, info@duerruk.com

# 1.4 Emergency telephone number

INT: +49 6132 84463 (24 h/7 d)

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Although there is no labelling required for this product, we nevertheless advise observation of the safety recommendations.

# Classification according to Regulation (EC) No 1272/2008 [CLP]

None

# 2.2 Label elements

# Labelling according to Regulation (EC) No. 1272/2008 [CLP]

#### **Precautionary statements**

P280 Wear protective gloves and eye/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container to hazardous or special waste collection point.

#### Special rules for supplemental label elements for certain mixtures

EUH210 Safety data sheet available on request.

#### 2.3 Other hazards

None

Page: 1 / 10

# according to Regulation (EC) No. 1907/2006 (REACH)

**Trade name :** Automat XR/C+ Fixer concentrate

**Revision date:** 09.09.2020 **Version (Revision):** 2.0.0 (1.0.0)

**Print date:** 16.12.2020

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

#### **Description**

Automat XR/C+ Fixer concentrate contains ammonium thiosulfate, organic acids and auxiliary agents in aqueous solution.

#### **Hazardous ingredients**

ACETIC ACID; REACH No.: 01-2119475328-30; EC No.: 200-580-7; CAS No.: 64-19-7

Weight fraction :  $\geq 1 - < 5 \%$ 

Classification 1272/2008 [CLP]: Flam. Liq. 3; H226 Met. Corr. 1; H290 Skin Corr. 1A; H314 Eye Dam. 1; H318

**Additional information** 

Full text of H- and EUH-phrases: see section 16.

# **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

#### **General information**

Remove contaminated, saturated clothing immediately. When in doubt or if symptoms are observed, get medical advice.

#### Following inhalation

Provide fresh air. In case of respiratory tract irritation, consult a physician.

#### In case of skin contact

Wash with plenty of water. When in doubt or if symptoms are observed, get medical advice.

#### After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

#### After ingestion

If swallowed, immediately drink: Water Never give anything by mouth to an unconscious person or a person with cramps. Do NOT induce vomiting. Call a physician immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

No information available.

# 4.3 Indication of any immediate medical attention and special treatment needed

None

## **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

# Suitable extinguishing media

Carbon dioxide (CO2) Extinguishing powder Water spray jet Water mist The product itself does not burn. Co-ordinate fire-fighting measures to the fire surroundings.

#### Unsuitable extinguishing media

Full water jet

# 5.2 Special hazards arising from the substance or mixture

None known.

### **Hazardous combustion products**

None known.

## 5.3 Advice for firefighters

Adapt protective equipment to surrounding fire.

#### Special protective equipment for firefighters

Adapt protective equipment to surrounding fire.

Page: 2 / 10

# according to Regulation (EC) No. 1907/2006 (REACH)

**Trade name :** Automat XR/C+ Fixer concentrate

**Revision date:** 09.09.2020 **Version (Revision):** 2.0.0 (1.0.0)

**Print date :** 16.12.2020

#### **SECTION 6: Accidental release measures**

# 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protection equipment. See protective measures under point 7 and 8.

## For non-emergency personnel

Use personal protection equipment. See protective measures under point 7 and 8.

#### For emergency responders

#### **Personal protection equipment**

See protective measures under point 7 and 8.

#### 6.2 Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

#### 6.3 Methods and material for containment and cleaning up

#### For cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal.

#### Other information

Treat the recovered material as prescribed in the section on waste disposal.

#### 6.4 Reference to other sections

None

# **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Keep/Store only in original container. Please note safety instructions and directions for use on the drum. Handle and open container with care. Provide adequate ventilation. Do not breathe vapour/aerosol.

#### **Protective measures**

## Measures to prevent fire

Usual measures for fire prevention. When using do not smoke.

# 7.2 Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep/Store only in original container. Keep container tightly closed. Keep in a cool, well-ventilated place. Do not store in temperatures below 5  $^{\circ}$ C.

# Hints on joint storage

Store the foodstuffs separately.

#### 7.3 Specific end use(s)

None

# **SECTION 8: Exposure controls/personal protection**

# 8.1 Control parameters

#### Occupational exposure limit values

ACETIC ACID ; CAS No. : 64-19-7

Limit value type (country of origin): STEL (EC)

Limit value: 20 ppm / 50 mg/m<sup>3</sup>

Version: 20.06.2019 Limit value type (country of origin): STEL ( EC )

Limit value: 50 mg/m<sup>3</sup> / 20 ppm

Limit value type (country of origin): TWA ( EC )

Limit value: 10 ppm / 25 mg/m<sup>3</sup>

Page: 3 / 10

(EN / GB)

# according to Regulation (EC) No. 1907/2006 (REACH)

**Trade name :** Automat XR/C+ Fixer concentrate

**Revision date:** 09.09.2020 **Version (Revision):** 2.0.0 (1.0.0)

**Print date :** 16.12.2020

Version : 20.06.2019 Limit value type (country of origin) : TWA (EC)

#### **DNEL-/PNEC-values**

There are no data available on the preparation itself.

#### **DNEL/DMEL**

ACETIC ACID; CAS No.: 64-19-7

Limit value type : DNEL Consumer (local)

Exposure route: Inhalation
Exposure frequency: Long-term
Limit value: 25 mg/m³

Limit value type : DNEL Consumer (local)

Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : 25 mg/m³

Limit value type : DNEL worker (local)

Exposure route: Inhalation
Exposure frequency: Long-term
Limit value: 25 mg/m³

Limit value type : DNEL worker (local)

Exposure route: Inhalation
Exposure frequency: Short-term
Limit value: 25 mg/m³

**PNEC** 

ACETIC ACID; CAS No.: 64-19-7

Limit value type : PNEC (Aquatic, freshwater)

Limit value: 3,058 mg/l

Limit value type : PNEC (Aquatic, marine water)

Limit value : 0,3058 mg/l
Limit value type : PNEC (Industrial)

Exposure route: Soil
Limit value: 0,478 mg/kg

Limit value type : PNEC (Sediment, freshwater)

Limit value : 11,36 mg/kg

Limit value type : PNEC (Sediment, marine water)

Limit value : 1,136 mg/kg

Limit value type : PNEC (Sewage treatment plant)

Limit value : 85 mg/l

## 8.2 Exposure controls

#### **Personal protection equipment**

# **Eye/face protection**

Eye glasses with side protection DIN EN 166

#### Skin protection

# **Hand protection**

Short-term exposure (Level 2: < 30 min): disposable gloves to EN374 category III, e.g. nitrile rubber, material thickness 0.1 mm.

Long-term exposure (Level 6: < 480 min): protective gloves to EN374 category III, e.g. nitrile rubber, material thickness 0.7 mm.

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. AUS/NZ: Wear impervious rubber gloves (AS2161).

#### **Body protection**

Body protection: not required.

Page: 4 / 10

# according to Regulation (EC) No. 1907/2006 (REACH)

**Trade name :** Automat XR/C+ Fixer concentrate

**Revision date:** 09.09.2020 **Version (Revision):** 2.0.0 (1.0.0)

**Print date :** 16.12.2020

## **Respiratory protection**

Usually no personal respirative protection necessary.

#### **General information**

Keep away from food, drink and animal feedingstuffs. Avoid contact with skin, eyes and clothes. Remove contaminated, saturated clothing. Wash hands before breaks and after work. Separate storage of work clothes. When using do not eat, drink, smoke, sniff.

not determined

### Other protection measures

Provide adequate ventilation.

# **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

Appearance: Liquid
Colour: colourless
Odour: Acetic acid
Safety characteristics

Melting point/freezing point:

Initial boiling point and boiling range:

Decomposition temperature:

(1013 hPa)

not determined not determined

Flash point:

Auto-ignition temperature:

Lower explosion limit:

Upper explosion limit:

(20.96)

1.30 1.308 a (6.96)

(1013 hPa)

Maximum VOC content (EC): 5 Wt %

Oxidising liquids:

Explosive properties:

Corrosive to metals:

Not applicable.

Not corrosive to metals.

### 9.2 Other information

None

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

None, if handled according to order.

## 10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7). Exothermal reaction with alkalis.

# 10.3 Possibility of hazardous reactions

Exothermal reaction with alkalis.

# 10.4 Conditions to avoid

No information available.

# 10.5 Incompatible materials

None known.

#### 10.6 Hazardous decomposition products

None known.

Page: 5 / 10

# according to Regulation (EC) No. 1907/2006 (REACH)

**Trade name :** Automat XR/C+ Fixer concentrate

**Revision date:** 09.09.2020 **Version (Revision):** 2.0.0 (1.0.0)

**Print date:** 16.12.2020

# **SECTION 11: Toxicological information**

# 11.1 Information on toxicological effects

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

**Acute oral toxicity** 

Parameter: ATEmix calculated

Exposure route : Oral
Effective dose : not relevant

Parameter: LD50 ( ACETIC ACID ; CAS No. : 64-19-7 )

Exposure route : Oral
Species : Rat
Effective dose : 3310 mg/kg
Practical experience/human evidence

Avoid contact with skin and eyes.

Acute dermal toxicity

Parameter: ATEmix calculated

Exposure route : Dermal Effective dose : not relevant

Parameter: LD50 ( ACETIC ACID ; CAS No. : 64-19-7 )

Exposure route: Dermal
Species: Rabbit
Effective dose: 1060 mg/kg

Acute inhalation toxicity

Parameter: ATEmix calculated
Exposure route: Inhalation (vapour)
Effective dose: not relevant

Parameter: LC50 ( ACETIC ACID ; CAS No. : 64-19-7 )

Exposure route: Inhalation
Species: Mouse
Effective dose: 5620 mg/l

Parameter: LD50 ( ACETIC ACID ; CAS No. : 64-19-7 )

Exposure route: Inhalation
Species: Rat
Effective dose: 4000 mg/l

**Corrosion** 

Based on available data, the classification criteria are not met.

# Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

#### CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

**STOT-single exposure** 

Based on available data, the classification criteria are not met.

**STOT-repeated exposure** 

Based on available data, the classification criteria are not met.

**Aspiration hazard** 

Page: 6 / 10

# according to Regulation (EC) No. 1907/2006 (REACH)

**Trade name :** Automat XR/C+ Fixer concentrate

**Revision date:** 09.09.2020 **Version (Revision):** 2.0.0 (1.0.0)

**Print date :** 16.12.2020

Based on available data, the classification criteria are not met.

#### 11.5 Additional information

The classification was carried out according to the calculation method of Regulation No. (EC) 1272/2008 [CLP].

# **SECTION 12: Ecological information**

## 12.1 Toxicity

#### **Aquatic toxicity**

Based on available data, the classification criteria are not met.

Acute (short-term) fish toxicity

Parameter: LC50 ( ACETIC ACID ; CAS No. : 64-19-7 )

Species: Leuciscus idus (golden orfe)
Evaluation parameter: Acute (short-term) fish toxicity

Effective dose : 400 - 500 mg/l

Exposure time: 48 h

Parameter: LC50 ( ACETIC ACID ; CAS No. : 64-19-7 )

Species: Lepomis macrochirus (Bluegill)
Evaluation parameter: Acute (short-term) fish toxicity

Effective dose : 75 mg/l Exposure time : 96 h

Parameter: LC50 ( ACETIC ACID ; CAS No. : 64-19-7 )
Species: Pimephales promelas (fathead minnow)

Evaluation parameter : Acute (short-term) fish toxicity

Effective dose : 79 mg/l Exposure time : 96 h Acute (short-term) toxicity to crustacea

Parameter: EC50 ( ACETIC ACID ; CAS No. : 64-19-7 )
Species: Daphnia magna (Big water flea)
Evaluation parameter: Acute (short-term) daphnia toxicity

Effective dose : 95 mg/l Exposure time : 24 h

Acute (short-term) toxicity to aquatic algae and cyanobacteria

Parameter : EC0 ( ACETIC ACID ; CAS No. : 64-19-7 )

Evaluation parameter : Acute (short-term) algae toxicity

Effective dose : 65 mg/l Exposure time : 85 h

Toxicity to microorganisms

Parameter: EC0 ( ACETIC ACID ; CAS No. : 64-19-7 )

Species: Pseudomonas putida
Evaluation parameter: Bacteria toxicity
Effective dose: 2850 mg/l
Exposure time: 16 h

# 12.2 Persistence and degradability

# **Biodegradation**

No data available.

## 12.3 Bioaccumulative potential

No information available.

# 12.4 Mobility in soil

## **Distribution**

There are no data available on the preparation itself.

#### 12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

Page: 7 / 10

# according to Regulation (EC) No. 1907/2006 (REACH)

**Trade name :** Automat XR/C+ Fixer concentrate

**Revision date:** 09.09.2020 **Version (Revision):** 2.0.0 (1.0.0)

**Print date :** 16.12.2020

#### 12.6 Other adverse effects

No information available.

#### 12.7 Additional ecotoxicological information

Do not allow to enter into surface water or drains.

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

## **Directive 2008/98/EC (Waste Framework Directive)**

After intended use

#### **Disposal operations**

Dispose according to legislation. Consult the appropriate local waste disposal expert about waste disposal.

#### **Recovery operations**

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself

## Waste codes/waste designations according to EWC/AVV

Concentrate/larger quantities: 09 01 04\* fixer solutions.

## **SECTION 14: Transport information**

#### 14.1 UN number

No dangerous good in sense of these transport regulations.

# 14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

# 14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

## 14.4 Packing group

No dangerous good in sense of these transport regulations.

#### 14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

## 14.6 Special precautions for user

None

## 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

## **SECTION 15: Regulatory information**

# Safety, health and environmental regulations/legislation specific for the substance or mixture

**EU** legislation

#### Authorisations and/or restrictions on use

**Restrictions on use** 

Use restriction according to REACH annex XVII, no.: 40

#### **National regulations**

## **Restrictions of occupation**

None

# 15.2 Chemical safety assessment

For this mixture a chemical safety assessment has not been carried out.

# **SECTION 16: Other information**

Page: 8 / 10

# according to Regulation (EC) No. 1907/2006 (REACH)

**Trade name :** Automat XR/C+ Fixer concentrate

**Revision date:** 09.09.2020 **Version (Revision):** 2.0.0 (1.0.0)

**Print date :** 16.12.2020

# 16.1 Indication of changes

08. Occupational exposure limit values · 11. Acute toxicity · 11. Corrosion · 11. Respiratory or skin sensitisation · 11. Carcinogenicity · 11. Germ cell mutagenicity · 11. Reproductive toxicity · 11. STOT-single exposure · 11. STOT-repeated exposure · 11. Aspiration hazard · 12. Aquatic toxicity · 15. Restrictions on use

#### 16.2 Abbreviations and acronyms

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimates

CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CMR = Carcinogen, Mutagen or Reproductive toxicant

CO<sub>2</sub> = Carbon dioxide

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EC = European Commission

EC50 = Half maximal effective concentration

EN = European Standard (Norm)

EU = European Union

EUH statement = CLP-specific Hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

H statement = GHS Hazard statement

IATA = International Air Transport Association ICAO-TI = International Civil Aviation Organization-Technical Instructions

IMDG = International Maritime Dangerous Goods

LC50 = Median lethal concentration

LD50 = Median lethal dose

LogPow = Logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol

of 1978. ("Marpol" = marine pollution)

NOEC/NOEL = No observed effect concentration/level

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No.

1907/2006]

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RMM = Risk Management Measure

RRN = REACH Registration Number

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

SVHC = Substances of Very High Concern

TLV/STEL = Threshold limit value/short-term exposure limit

TLV/TWA = Threshold limit value/time weighted average

UN = United Nations

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

# 16.3 Key literature references and sources for data

None

# $^{16.4}$ Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

The classification was carried out according to the calculation method of Regulation No. (EC) 1272/2008 [CLP].

## 16.5 Relevant H- and EUH-phrases (Number and full text)

H226 Flammable liquid and vapour. H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

# 16.6 Training advice

Page: 9 / 10

# according to Regulation (EC) No. 1907/2006 (REACH)

**Trade name :** Automat XR/C+ Fixer concentrate

**Revision date :** 09.09.2020 **Version (Revision) :** 2.0.0 (1.0.0)

**Print date :** 16.12.2020

None

# 16.7 Additional information

Notice the directions for use on the label.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Page: 10 / 10